



PriceVision® Product Information

SPECIFICATIONS

Digit height (inches)	9, 12, 15, 18, 24, 36, 48, 60 (Custom sizes upon request)	
Standard digit format	High definition seven segment (Custom digit format upon request)	
Price display range	FMDXX-GSX FMDXX-GSX-C FMDXX-GSX-CN FMDXX-GSX-SA	0.00 ⁹ to 9.99 ⁹ or 0.00 ⁹ / ₁₀ to 9.99 ⁹ / ₁₀ 000.0 to 999.9 00.00 to 99.99
LED type	Discrete	
LED color	Red, Amber, Blue, Green, White (limited availability)	
Brightness	Direct sunlight visibility	
Viewing angle	Up to 140 degrees horizontal	
Operating temperature	-40°F – +185°F	
Luminosity control	Automatic proportional brightness control with 256 levels and SmartNight field calibration capability	
Display controller	Built-in embedded with industrial performance and reliability for each grade display unit	
Data Retention	Unlimited in time in the event of external power interruption	
Connectivity methods	Direct cable, wireless, internet, satellite	
Communication	Standard RS-232 (RS-422, RS-485, Ethernet)	
PriceVision input device	Integrated control unit with LCD and price confirmation capability	
Automatic operation option	Direct interface with any POS system	
Price change confirmation	Yes	
Sleep mode	Yes	
Zero \$ suppression option	Yes	
Power pack	Switching power supply mounted inside weather-proof enclosure	
Operating voltage	Input: 100-240V AC	
Price panel	Weather-proof low profile aluminum enclosure provides maximum protection for electronic components	
Front screen	Non-glare, UV-protected polycarbonate	